

HID Fixtures

Bell Lighting Technologies Inc.

LF / WP Series



Wall / Pole Mounting - Dry Application

The LU/WP Series comes fully assembled and complete with:

- Quad Series Ballast, 120/208/240/277 V or Tri-Tap 120/277/347 V in 50 or 60 Hz."
- 4mm Tempered Safety Glass panel or optional 4mm Tempered Pinhead Safety Glass.
- Pre-wired, including a 1m Pigtail."
- Wall / Pole mount bracket kit."
- 7 fixture positions, providing 190° of rotation using a quick release pin.



The LF/WP Series is manufactured from the highest quality ISO Marine Aluminum and is completely welded for superior structural strength. Alternate optional equipment may be available upon request.

Metal Halide	NSN
250 Watt LF250 WP-DR-MH	
400 Watt LF400 WP-DR-MH	
1000 Watt LF1000 WP-DR-MH	
1000 Watt LF1000 WP-DR-MH Compact	
High Pressure Sodium	
250 Watt LF250 WP-DR-HPS	
400 Watt LF400 WP-DR-HPS	
600 Watt LF600 WP-DR-HPS	
1000 Watt LF1000 WP-DR-HPS	

LF-WP-DR 250 / 400 / 600
LF-WP-DR 1000 Compact



40.6 cm x 58.4 cm x 40.9 cm
Approximate Weight 17.3 Kg / 38 lbs
(LU 1000 Compact 27.3 Kg / 60 lbs)

LF-WP-DR 1000



55.9 cm x 76.2 cm x 40.9 cm
Approximate Weight 27.3 Kg / 60 lbs